

# Disc harrows with hydraulic folding RC-PH up to 240 HP

High performance and great penetration capacity

The RC-PH range combines great penetration capacity, construction robustness and high performance with easy transport.



### A. Control and transport wheels

The large wheel unit permits precision control over the work depth and great safety and stability during transport.



### B. Stress absorption and horizontality adjustment

Two robust springs absorb the stress between the tractor and the harrow. By a screw, the horizontality is easily adjusted depending on the coupling height to the tractor.



### C. Multiple drawbar adjustment

The position of the drawbar can be adjusted both in height and horizontally to optimise the ratio between the traction power and the harrow.



### D. Rotation points without wear

The six rotation, folding and adjustment points of the working angle, rotate on bearings to facilitate the rotation.




### E. Easy adjustment of working angle

The working angle of the disc bodies is easily adjusted with a screw (hydraulically optional), which secures the working position.



### F. Easy to fold away

A double frame permits easy hydraulic folding of the disc bodies from the tractor cab to 2,50 transport width. A lock valve secures the position of the bodies in working position or transport position as well as a safety bolt.



### G. Reinforced bearing blocks

2 roller bearings and double sealing increase the service life of the bearings and reduce maintenance costs.

	Number of discs		Disc to disc clearance (mm)		Working width (mm)		Number of bearing blocks		Weight (kg)		Power (HP)		Tyres	
	26"	28"	26"	28"	26"	28"	26"	28"	26"	28"	26"	28"	26"	28"
<b>24-RC+PH</b>	—	24	—	270	—	3.160	—	4+4	—	4.000	—	115	—	400/60-15"
<b>26-RC+PH</b>	26	26	240	270	3.050	3.430	4+4	4+4	3.700	4.100	115	130	400/60-15"	400/60-15"
<b>28-RC+PH</b>	28	28	240	270	3.300	3.700	4+4	4+4	3.800	4.200	130	140	400/60-15"	400/60-15"
<b>30-RC+PH</b>	30	30	240	270	3.550	3.970	4+4	4+4	3.900	4.300	140	150	400/60-15"	400/60-15"
<b>32-RC+PH</b>	32	32	240	270	3.800	4.240	4+4	6+6	4.000	4.400	150	160	400/60-15"	400/60-15"
<b>34-RC+PH</b>	34	34	240	270	4.050	4.510	6+6	6+6	4.100	4.600	160	170	400/60-15"	400/60-15"
<b>36-RC+PH</b>	36	36	240	270	4.300	4.780	6+6	8+8	4.200	4.700	170	180	400/60-15"	400/60-15"
<b>38-RC+PH</b>	38	—	240	—	4.550	—	8+8	—	4.300	—	180	—	400/60-15"	—
<b>40-RC+PH</b>	40	40	240	270	4.800	5.320	8+8	8+8	4.400	4.800	190	200	400/60-15"	400/60-15"
<b>42-RC+PH</b>	42	—	240	—	5.050	—	8+8	—	4.500	—	200	—	400/60-15"	—
<b>44-RC+PH</b>	—	28	—	270	—	5.880	—	8+8	—	5.300	—	240	—	500/50-17"