

L/R series light ploughs up to 90 HP

Great turning capacity with low power

The Lacasta plough line, with a long tradition, is designed for low power, articulated and fixed tractors. Great soil penetration capacity with minimum total weight favours power savings.



Model LM 30 HP



	Share width	Working width (cm)	Depth width (cm)	Total height (cm)	Weight (kg)	Power (HP)	Skimmers	Safety bolt	Side adjustment	Hydraulic turn over	1 Point linkage
LM 18 HP	8"	20	20	86	95	15-20	Op.	—	—	Op.	Op.
LM 21 HP	8"	20	25	100	125	20-30	Op.	—	—	Op.	Op.
LM 30 HP	9"	22,5	25	107	142	30-40	Op.	Op.	Op.	Op.	Op.
LM 40 HP	9"	22,5	30	115	175	40-45	Op.	Incl.	—	Op.	Op.
LB 21 HP	8"	40	20	93	155	20-30	—	Incl.	—	Op.	Op.
LB 30 HP	8"	40	25	100	165	30-40	—	Incl.	—	Op.	Op.
LB 40 HP	9"	45	25	105	210	40-45	—	Incl.	—	Op.	Op.
RM 10"	10"	25	30	118	220	35-45	Op.	Incl.	Op.	Incl.	—
RM 12"	12"	30	35	128	295	45-55	Op.	Incl.	—	Incl.	—
RM 14"	14"	35	40	138	340	55-70	Op.	Incl.	—	Incl.	—
RM 16"	16"	40	45	150	345	60-75	Op.	Incl.	—	Incl.	—
RM 18"	18"	45	45	160	475	70-90	—	Incl.	—	Incl.	—
RB 10"	10"	50	25	110	295	35-45	—	Incl.	—	Incl.	—
RB 12"	12"	60	30	118	390	45-55	—	Incl.	—	Incl.	—
RB 14"	14"	70	35	132	445	55-70	—	Incl.	—	Incl.	—
RB 16"	16"	80	40	145	525	65-80	Op.	Incl.	—	Incl.	—
RB 17"	17"	85	40	150	535	75-90	Op.	Incl.	—	Incl.	—

OPTIONS Serie L: Safety bolt, Hydraulic turn over, Side adjustment, Two-point hitch.
Serie R: Skimmers, Hydraulic turnover.




A. Easy soil penetration
 The design of the tip and ploughshare favours rapid penetration and soil tillage with minimum power requirements.



B. Different kinds of headstocks
 The different heads allow a three-point hitch or two-point hitch, depending on the kind of tractor.



C. Manual or hydraulic turn over
 Turning can be manual, semi-automatic or hydraulic, optional depending on the model (see Table).



D. Safety bolt
 The mouldboard bodies are equipped with a safety bolt (starting with the LM 40 series).



E. Great turning capacity
 The mouldboards, which we manufacture ourselves, guarantee quick circulation of the soil and great turning capacity.



F. Optional skimmers
 Optionally, skimmers can be installed for large quantities of plant remains. They pre-turn the surface before the mouldboard.