

# Mixed TRB-F shredders up to 115 HP

High shredding intensity

Mixed series for agricultural applications and forestry work. Light and with little power demand, it is able to intensively shredding plant residues.



### A. Large diameter rotor

The special 400 mm rotor with 360° floating hammers allows for the extremely effective, intense shredding of plant residues with a diameter of up to 10 mm.



Hammer N°1



### B. Anti-wear steel chassis

Chassis, anti-projection plates and counter hammers made of special, non-wear steel to resist the circulation of a large amount of plant remains and foreign bodies during the most demanding work.



### C. Safe drive

The sealed gearbox bathed in oil ensures intensive work with minimum maintenance costs.



### D. Moveable three-point linkage

Cat II three-point coupling is equipped with hydraulic side movement as standard.



### E. Roller control height

The rear roller controls the working height of the rotor by means of the different positions. The greaser is completely protected against the adversities of the land.

SPECIFICATIONS	TRBF-150	TRBF-180	TRBF-200	TRBF-220
Working width (cm)	150	180	200	220
Transport width (cm)	170	200	220	240
r.p.m.	540	540	540	540
N° of hammers	14	16	18	20
Weight (Kg)	780	880	950	1020
Power (HP)	65-80	80-95	85-100	95-115